

# EPIC VISION

## Classic 300mm



**Weight:** 2410 grams / 5.31 lb  
**Overall length:** 750 mm / 29.53 in  
**Aluminum air cylinder:** 125cc  
**Plenum:** 50cc  
**Mil-Spec adjustable AR-15 stock**  
**Barrel length:** 300 mm / 11.81 in  
**Caliber:** .177 / .22 / .25

## CFB 300mm



**Weight:** 2570 grams / 5.67 lb  
**Overall length:** 750 mm / 29.53 in  
**Carbon Fiber Bottle:** 300cc  
**Plenum:** 50cc  
**Mil-Spec adjustable AR-15 stock**  
**Barrel length:** 300 mm / 11.81 in  
**Caliber:** .177 / .22 / .25

## Classic 420mm



**Weight:** 2740 grams / 6.04 lb  
**Overall length:** 870 mm / 34.25 in  
**Aluminum air cylinder:** 205cc  
**Plenum:** 50cc  
**Mil-Spec adjustable AR-15 stock**  
**Barrel length:** 420 mm / 16.54 in  
**Caliber:** .177 / .22 / .25

## CFB 420mm



**Weight:** 2910 grams / 6.42 lb  
**Overall length:** 870 mm / 34.25 in  
**Aluminum air cylinder:** 580cc  
**Plenum:** 50cc  
**Mil-Spec adjustable AR-15 stock**  
**Barrel length:** 420 mm / 16.54 in  
**Caliber:** .177 / .22 / .25



# EPIC VISION specs sheet

## MAGAZINE CAPACITY (depth 15mm)

cal.177: 16 shots  
cal.22: 13 shots  
cal.25: 11 shots  
cal.30: 9 shots

## TRIGGER RESISTANCE

from 180 up to 650 grams (from 6.35 oz up to 1.43 lb)

## SHOT CAPACITY (Airtube / Bottle)

300mm 4,5 (.177) ≈ up to 165 / 380 shots  
420mm 4,5 (.177) ≈ up to 310 / 900 shots

300mm 5,5 (.22) ≈ up to 190 / 450 shots  
420mm 5,5 (.22) ≈ up to 325 / 915 shots

300mm 6,35 (.25): ≈ up to 205 / 490 shots

420mm 6,35 (.25): ≈ up to 340 / 950 shots

\*measured with 16 Joules / 12ft.lb version with classic valve

## MAX ENERGY (FAC valve and regulator pressure 170 BAR)

300mm 4,5 (.177) ≈ up to 40 Joules / 29.5 ft·lb (19 shots with airtube / 45 shots with 300cc bottle)  
420mm 4,5 (.177) ≈ up to 50 Joules / 36.9 ft·lb (35 shots with airtube / 105 shots with 580cc bottle)

300mm 5,5 (.22) ≈ up to 60 Joules / 44.3 ft·lb (17 shots with airtube / 40 shots with 300cc bottle)  
420mm 5,5 (.22) ≈ up to 72 Joules / 53.1 ft·lb (30 shots with airtube / 85 shots with 580cc bottle)

300mm 6,35 (.25) ≈ up to 70 Joules / 51.6 ft·lb (13 shots with airtube / 36 shots with 300cc bottle)  
420mm 6,35 (.25) ≈ up to 90 Joules / 66.4 ft·lb (22 shots with airtube / 65 shots with 580cc bottle)

## FAC VALVE OPENING FOR EACH BARREL LENGTH (from factory settings):

300mm: 1,5mm  
420mm: 1,8mm  
550mm: 2,1mm  
700mm: .177: 2,1mm / .22: 2,5mm / .25: 2,7mm

## MAX ENERGY for 700mm versions (without any upgrades)

4,5 (.177) ≈ up to 78 Joules / 57.5 ft·lb  
5,5 (.22) ≈ up to 110 Joules / 81.1 ft·lb  
6,35 (.25) ≈ up to 130 Joules / 95.9 ft·lb

\*measured with 170 BAR regulator pressure, without any additional plenum, with CZUB barrel

- Adjustable AR-15 stock
- Built-in Quick Detach Sling Swivel
- Convertible AR-15 grip
- Covered filling port
- External hammer spring adjuster
- High-Power assisted valve
- Picatinny rail with a 30 MOA incline
- Ambidextrous side lever
- Max fill pressure 300 BAR / 4 350 PSI

- CZUB non-choked barrel 12 grooves with 17,7" twist rate
- Lothar Walther polygonal non-choked barrel 6 grooves with 17,7" twist rate
- Both pressure gauges on the side
- Interchangeable calibers
- Fully adjustable trigger mechanism
- Picatinny stock adapter / MDT AR-15 stock adapter
- Integrated bottom picatinny rail
- Most consistent air rifle with assisted valve on the market
- Externally adjustable regulator

